

## BSL SERIES


**BSL-5045L**

SEMIAUTOMATIC L-SEAL CUTTING MACHINE


**BSL-5045LA**

PNEUMATIC L-SEAL CUTTING MACHINE

**Description:**

When the sealing & cutting cycle is complete, the conveyor discharges the product into the shrink tunnel automatically. The shrink tunnel is equipped to reach higher capacity.

**Features:**

1. Safety device that prevents the sealing knife from overheating and guarantees operator's safety.
2. Nano-fiber cutter holder and antisticking thermostable nichrome cutter that ensure good sealing without cracking or coking.
3. Conveyor belt height is adjustable via handwheel.
4. Time relay that ensures accurate control of sealing & cutting times.
5. Electro-magnetic hold-down provides more secure seal.
6. Sliding roll holder, fully adjustable for different sized rolls of film (max. width:550mm).
7. Return cylinder equipped to control sealing & cutting frame.
8. Model BSL-5045LA is equipped with pneumatic mechanism.

**Application:**

1. The machine is designed to pack electronic products, hardware, software, foodstuff, printing, pharmacy, floor, ceramics, etc. in small amount.
2. It is suitable for all kinds of packaging materials, such as PVC, POF, PP, etc.

**BSL-5045L**
**BSL-5045LA**

(V/Hz) Voltage	220/50	
(Kg/cm <sup>2</sup> ) Air Pressure Required	--	6-8
(Kw) Power	1.2	
(PCS/h) Capacity	800-1200	
(LxWxH) (mm) Max. Packing Size	450x400x300	
(LxH) (mm) Max. Sealing & Cutting Size	500x450	
(LxWxH) (mm) External Dimensions	1560x757x1040	
(Kg) Net. Weight	125	135