


**BSF-6030X**

SEMIAUTOMATIC SLEEVE SEALING MACHINE


**BSF-6030X+BS-5540M**

SEMIAUTOMATIC SLEEVE SEALING MACHINE WITH SHRINK TUNNEL

## BSF-6030X

**Description:**

BSF-6030X semiautomatic sleeve sealing machine is a type of economic one among BSF series, simple operation, push the products manually or pneumatically, sealing the film and the products enter the shrink tunnel automatically, and used PE film to pack products.

**Features:**

1. BSF-6030X adopts the imported air-cylinder, assure stable pushing and sealing.
2. Adopts specially designed sealing cutter, results in perfect sealing line, avoid the film sticking the cutter.
3. The covered cylinder setting enhance the convenience for the operator; with rear pressing device assure even light product without any shifting.
4. The front frame is adjustable according to different product sizes.

**Application:**

1. BSF-6030X semiautomatic sleeve sealing machine used for packing beverage, beer and mineral water etc with or without a tray; also suitable for shrink wrapping products such as electric appliance, auto spares, furniture and floor board etc.
2. It's suitable for all kinds of shrink films such as PVC, POF, PP, PE etc.

### BSF-6030X

电源 (V/Hz) Voltage	380/50 (3PH)
功率 (kw) Power	1.5
工作气压 (kg/cm <sup>2</sup> ) Compressed Air	6.0
最大包装尺寸 (L×W×H) (mm) Max. Packing Size	550×290×380
最大封口长度 (mm) Sealing & Cutting Length (mm)	650
包装速度 (Trays/min) Capacity	0-12
进科工作水平高度 (mm) Infeed Conveyor Height	850 ± 50
适用膜 (mm) Film Used	PVC、PE
外形尺寸 (L×W×H) (mm) External Dimensions	1370×920×1800
净重 (kg) Net Weight	220